

# Axcient x360Recover Appliance Specifications

	Pico	Eco			Mini							Rack			
	Pico-1500	Eco-1500	Eco-3000	Eco-6000	Mini-1500	Mini-3000	Mini-6000	Mini-12000	Mini-1500-SSD	Mini-3000-SSD	Mini-6000-SSD	Rack-4500	Rack-9000	Rack-18000	Rack-27000
Available Capacity	1.8 TB	1.8 TB	3.5 TB	7 TB	1.8 TB	3.5 TB	7 TB	14 TB	1.8 TB	3.5 TB	7 TB	5.3 TB	10.6 TB	21 TB	36 TB
Recommended 85% as Usable Capacity	1.5 TB	1.5 TB	3 TB	6 TB	1.5 TB	3 TB	6 TB	12 TB	1.5 TB	3 TB	6 TB	4.5 TB	9 TB	18 TB	27 TB
Field Upgradable to: (Total Usable)	-	-			3 TB	6 TB	12 TB	-				9 TB	18 TB	27 TB	54 TB
Storage Redundancy <sup>2</sup>	-	RAIDZ (Mirrored)			RAIDZ (Mirrored)				RAIDZ1 (N+1 Parity)						
CPU	Intel i3-1315U	2-core Intel Pentium Gold			6-core Intel Xeon							12-core Intel Xeon	2x 12-core Intel Xeon		
RAM	16 GB	16 GB			32 GB		64 GB		32 GB		64 GB	64 GB	128 GB	256 GB	
Ram Field Upgrade	-	-			-							256 GB	512 GB		
RAM Field Upgrade Price	-	-			-							\$1980	\$3960	\$2640	
Shipping: RAM Field Upgrade	-	-			-							Ground \$35; 2 Day \$110; Next Day \$135			
1G Network	1 port	2 ports			2 ports							-			
10G Network	-	-			-							2 ports			
IPMI Remote Management	No	No			Yes							Yes			
Hot Swappable Drives	-	No			Yes							Yes			
Warranty	3 years Standard, Upgradable with an additional 1 or 2 years														
BDR Dimensions	5"x5"x 2"	5.3" x 8.7" x 13.5"			12.2" x 7.87" x 10.63"							2U Rack Mount			

Axcient recommends using no more than 85% of the Available Capacity for proper backup, replication, and recovery performance.

For models with all-SSD Storage, SSDs with special firmware from Axcient are supported; attempted use of non-Axcient SSDs will void all support and all warranties.

Please note that all sales are considered final. Once your order has been shipped, it cannot be canceled or returned.